

MALLEABLE PULLEY BLOCK (SWIVEL HOOK & CATCH)**Data Sheet****Break Load Certified: ✓****Conforms to BS EN 13157 Standard. ✓****AT A GLANCE**

Technical Specifications	
Material	Galvanised Malleable Iron
Construction	Swivel Hook & Catch
Colour	Grey
Shell Height (mm)	76 - 203
Sheave Diameter (mm)	45 - 137
Rope Diameter (mm)	12 - 28
Safe Working Load (Tonnes)	0.2 - 1.2
Manufactured In	Far East
Quality Standard	BS 13157 Standard

SAFE WORKING LOADS (SWL)

Break load test certified.

Single Sheave

Shell (inches/mm)	SWL (tonnes)	Sheave Dia. (mm)	Rope Dia. (mm)	Weight (kg)
3"/76mm	0.2	45	12	0.9
4"/102mm	0.4	60	16	1.5
5"/127mm	0.5	83	18	2.2
6"/152mm	1	92	24	4
8"/203mm	1.2	137	28	6

Double Sheave

Shell (inches/mm)	SWL (tonnes)	Sheave Dia. (mm)	Rope Dia. (mm)	Weight (kg)
3"/76mm	0.2	45	12	1
4"/102mm	0.4	60	16	2
5"/127mm	0.5	83	18	3.3
6"/152mm	1	92	24	5.5

Treble Sheave

Shell (inches/mm)	SWL (tonnes)	Sheave Dia. (mm)	Rope Dia. (mm)	Weight (kg)
4"/102mm	0.4	60	16	2.6
5"/127mm	0.5	83	18	5